Challenger Euro Rebate



Features

- Engineered with a unique 3D adjustability for ease of application and long term trouble-free performance
- Designed for modern chamfered profiles allowing fixings to the door to be supported in the eurogroove
- Available in four options 20/9mm, 20/13mm, 22/9mm and 22/13mm allowing 3D adjustment for lateral, height and compression while the door is closed
- Security of the pin is achieved by a concealed grub screw fixing protected by the closed door
- Available in White, Brown, Light Brown, Gold and Chrome finishes







Challenger Euro Rebate

Ordering Details				
Challenger Euro Rebate				
Product	Part No.			
Finish	Body	Flag 20/9	Flag 22/9	
Brown	DNCBBN0001	DNCGBN0001	DNGBNN0002	
Light Brown	DNCBLB0001	DNCGLB0001	DNCGLB0002	
Gold	DNCBGD0001	DNCGGD0001	DNCGGD0002	
Polished Gold	DNCBDG0001	DNCGDG0001	DNCGDG0002	
Polished Chrome	DNCBDC0001	DNCGDC0001	DNCGDC0002	
White	DNCBWH0001	DNCGWH0001	DNCGWH0002	
Finish	Flag 20/13 F		ag 22/13	
Brown	DNCGBN0	003 DN	CGBN0004	
Light Brown	DNCGLB0	003 DN	CGLB0004	
Gold	DNCGGD0003		CGGD0004	
Polished Gold	DNCGDG0003		CGDG0004	
Polished Chrome	DNCGDC0		DNCGDC0004	
White	DNCGWHO	0003 DN0	CGWH0004	
Accessories	Part No.			
Fixing Jig	DAJGBL0002			

Technical Information

Corrosion resistance

Meets the requirements of BS EN 1670:1998- White/Brown polyester powder paint and PVD Gold - 240 hours, Electroplated Gold - 96 hours

Operation

Endurance tested to over 50,000 cycles

Max Weight Per Door

3 hinges up to 100kg

Adjustability

Lateral +2mm/-2mm, Height +3mm, Compression -0.5mm/+0.5mm

Material Specification Hinge Body: Zinc alloy casting Euro Rebate Flag: Zinc alloy casting Coatings: Gold - Electroplated F913 Brown - Powder Paint RAL 8019 Light Brown - Powder Paint RAL 8001 Polished Gold and Chrome White - Powder coated White Hinge Pins: Stainless Steel Grub Screw: Stainless Steel

Black POM (Acetal)

White, brown or black POM (Acetal)

White, brown or black PA Nylon

Packaging


Hinge

Bushes:

Packers:

Cover Caps:

Individually packed, 24 hinges per box (Fixing screws not supplied)



Not to scale.

All dimensions are in mm and are nominal.

ERA reserves the right to change specification without notice
It is the responsibility of the door manufacturer to ensure that the finished product meets any required safety and performance specification

Maintenance

All moving parts should be lightly lubricated using a light non-acidic mineral oil (e.g. "3 in 1") twice per year and the surface cleaned with a soft damp cloth. The product may need to be adjusted and fixings tightened to ensure a satisfactory operation.