VS1 Classic Shootbolt Five Star Window Lock



Features

- A shootbolt locking system that has been designed to prevent attack on all 3
 planes back and forward, side to side, and up and down giving unattainable levels
 of security
- Non-croppable shootbolt locking system with a minimum of 8 points locking giving you the ultimate burglar detterent
- Tested by an independant test laboratory to over 6,000N force; more than double the requirement of the PAS24: 2012 security test
- Heavy duty bolt has up to 300% of the contact area against competitor shootbolts thus providing the most secure shootbolt on the market
- Patented docking system of the bolt into the keep ensures smooth operation and prevents sideways movements of the bolt when under attack
- Compatible with standard zinc espag keeps or the unique Power Brace keeps; that have a weather resistant nylon base combined with a 2mm hardened steel plate for significantly increased performance
- Upgrade to enhanced security with 3D locking pins fitted to the shootbolt and extended Power Brace keeps for upto 11 locking points
- Developed to withstand even the most determined intruder attack



		Snootb				
Ordering Details						
Bars						
Bars	Bar Length	No. of Cams	Part Code 20mm Backset	Part Code 22mm Backset		
1	190mm	0	WLFSVS1201	WLFSVS1221		
2	230mm	2	WLFSVS1202	WLFSVS1222		
3	400mm	2	WLFSVS1203	WLFSVS1223		
4	600mm	2	WLFSVS1204	WLFSVS1224		
5	800mm	3	WLFSVS1205	WLFSVS1225		
6	1000mm	3	WLFSVS1206	WLFSVS1226		
7	1200mm	3	WLFSVS1207	WLFSVS1227		
``	e see additional i	nformation shee	et for details on Sas	sh Rebate sizes)		
1	1200mm	2	WLFSVS1208	WLFSVS1228		















CASENENT WINDOWS

VS1 Classic Shootbolt Five Star Window Lock

Keeps			Part Code			
Profile	Gearbox Backset	Zinc Cam Keep (each)	Zinc Shoot Keeps (pair)	Composite Cam Keep (each)	Composite Shoot Keeps (pair)	Composite Shoot Keep Plate (pair)
Deceuninck 1800	20	WWKFSZEK13	WWKFSZSK13			
Deceuninck 2500	20			WWKFSC0818	WWKFSC0050	WWKFSP0090
Deceuninck 2800	20	WWKFSZEK13	WWKFSZSK13	WWKFSC0819	WWKFSC0050	WWKFSP0090
Deceuninck 3000	20	WWKFSZEK13	WWKFSZSK13			
Duraflex Diamond	20	WWKFSZEK01	WWKFSZSK01	WWKFSC0801	WWKFSC0001	WWKFSP0091
Eurocell Logik	20	WWKFSZEK10	WWKFSZSK10			
Eurocell Modus	20					
Eurocell Ultimate 70	20	WWKFSZEK07	WWKFSZSK07			
KBE		WWKFSZEK13	WWKFSZSK13			
Kommerling 70 Overlo/ Chamfer	22	WWKFSZEK13	WWKFSZSK13	WWKFSC0818	WWKFSC0050	WWKFSP0090
Liniar 70	22	WWKFSZEK13	WWKFSZSK13	WWKFSC0818	WWKFSC0050	WWKFSP0090
Plasmo Index 62	20	WWKFSZEK08	WWKFSZSK08			
Profile 22 70	20	WWKFSZEK16	WWKFSZSK16			
Rehau 706	22	WWKFSZEK02	WWKFSZSK02	WWKFSC0817	WWKFSC0053	WWKFSP0092
Rehau Tritec 60	20	WWKFSZEK04	WWKFSZSK04			
Rehau Calibre						
Schuco	20	WWKFSZEK12	WWKFSZSK12			
Spectus Elite	20	WWKFSZEK09	WWKFSZSK09	WWKFSC0817	WWKFSC0053	WWKFSP0092
Swish 70	22	WWKFSZEK11	WWKFSZSK11			
Synseal Legend 70	20			WWKFSC0817	WWKFSC0053	WWKFSP0092
Synseal Shield						
Synseal Synergy	20			WWKFSC0820	WWKFSC0054	WWKFSP0092
Veka Matrix 58 & 70	22	WWKFSZEK03	WWKFSZSK03			
WHS Halo Eclipse	22	WWKFSZEK13	WWKFSZSK13			
WHS Halo Rustique	22	WWKFSZEK13	WWKFSZSK13	WWKFSC0818	WWKFSC0050	WWKFSP0090
WHS Halo WHS 10	22	WWKFSZEK13	WWKFSZSK13	WWKFSC0818	WWKFSC0050	WWKFSP0090
Dummy Mullion - Deep			WWKFS0070			
Dummy Mullion - Shallow	1		WWKFS0071			

(NB: Centre Keeps - Keeps are handed, choose L (left) or R (right) on end of part code)

_					•
100	nnı	Cal	Int	ormat	rion.
		cai		OHIA	

Corrosion resistance

Meets the requirements of BS EN 1670:2007 Grade 5 (480 hours)

Operation

Tested in excess of 50,000

Performance

Tested independently to 6000n force, twice that of the usual PAS24:2012 test requirements $\,$

Material Specification

Bars:	High quality steel, Zinc plated, Trivalent passivated and seal
Keeps:	High quality steel, Zinc plated, Trivalent passivated and seal or Composite keeps with steel top plates
Shootbolts:	High quality steel

Packaging

Locks

20 locks per box

Keeps

20 keeps per box

Maintenance

All moving parts should be lightly lubricated using a light non-acidic mineral oil (e.g "3 in 1") twice per year and the surface cleaned with a soft damp cloth. The product may need to be adjusted and fixings tightened to ensure a satisfactory operation.

VS1 Classic Shootbolt Five Star Window Lock

Shootbolt Extensions and Optional Extras							
Profile	Part Code Shootbolt Extensions (pairs)	Part Code 3D Security 7-10mm Cams (each)	Part Code 3D Security 9-12mm Cams (each)	Part Code 3D Security Plates			
Deceuninck 1800	WLFSSB1100X						
Deceuninck 2500	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			
Deceuninck 2800	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			
Deceuninck 3000	WLFSSB1100X						
Duraflex Diamond	WLFSSB1500X	WLFS3D0001	WLFS3D0002	WWKFS3DP02			
Eurocell Logik	WLFSSB1100X WLFSSB1500X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			
Eurocell Modus							
Eurocell Ultimate 70	WLFSSB1500X						
KBE							
Kommerling 70 Overlo/ Chamfer	WLFSSB1500X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			
Liniar 70	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			
Plasmo Index 62	WLFSSB1500X						
Profile 22 70	WLFSSB1100X						
Rehau 706	WLFSSB1500X						
Rehau Tritec 60	WLFSSB1500X						
Rehau Calibre							
Schuco	WLFSSB1500X						
Spectus Elite	WLFSSB1500X	WLFS3D0001	WLFS3D0002	WWKFS3DP04			
Swish 70	WLFSSB1500X	1) // FC2D0004	\\# FC2D0002)) // // // COD DO /			
Synseal Legend 70	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP04			
Synseal Shield	WLFSSB1100X						
Synseal Synergy	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP05			
Veka Matrix 58 & 70	WLFSSB1100X						
WHS Halo Eclipse	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			
WHS Halo Rustique	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			
WHS Halo WHS 10	WLFSSB1100X	WLFS3D0001	WLFS3D0002	WWKFS3DP01			

NB: Shootbolt Extensions - 'X' within part code to be substituted with shootbolt bar number required. Usually 11mm = 13mm profile stack heights, 15mm = 17mm profile stack heights