

Monkey Tail Operating Stay Bar




Features


- **Moveable 10" Monkey Tail operating stay bar**
Add a classic finish to a heritage window
- **Non-handed, suitable for both left and right handed windows**
Reduced stock holding
- **Manufactured from die-cast zinc with specially formulated finish**
Harder wearing finish than traditional wrought ironmongery
- **Peg plates to suit Residence 9 window system**
Suitable for modern flush fitting PVC windows
- **Matching Monkey Tail Handle also available**
Create a perfectly matching heritage window
- **Supplied with colour coordinated screws**
Perfectly matching hardware, even down to the smallest detail




Hardex
Chrome



Hardex
Graphite



Hardex
Gold



Antique
Black

Monkey Tail Operating Stay Bar

Ordering Details

Product

Monkey Tail Operating Stay Bar

Finish

Part No.

Hardex Chrome	8A091
Hardex Gold	8A092
Hardex Graphite	8A090
Antique Black	8A089

Maintenance

For continued protection of the quality finish and appearance, Fab&Fix advise routine cleaning of all our external hardware. Moving parts should also be lightly lubricated at least twice a year. This procedure is particularly essential if products are used within a 25-mile radius of coastal areas or close proximity to building sites or large industrial areas, where more frequent cleaning may be required to prevent the accumulation of corrosive contaminants.

Packaging

Stay Bars

Individually bagged with screws and care instructions.
40 stay bars in an outer box.

Technical Information

Corrosion resistance

Meets the requirements of BS EN 1670:2007 Grade 5 (480 hours)

Material Specification

Stay Bar and Plates:	High quality Zinc for all finishes
Coatings:	Hardex Chrome, Hardex Gold, Hardex Graphite and Antique Black

All dimensions are in mm and are nominal.
Fab&Fix reserves the right to change specification without notice.
It is the responsibility of the window manufacturer to ensure that the finished product meets any required safety and performance specification.

